STAT:5400 Computing in Statistics

High Performance Computing

Nov. 13, 2017

Kate Cowles 374 SH, 335-0727 kate-cowles@uiowa.edu

Parallel computing in R: the snow package

- snow is a parallel computing package for R
- snow uses a master/worker model:
 - The user starts an ordinary R session as the master process.
 - This session creates (or connects to) a set of worker processes.
 - Jobs are sent to the worker processes and results are returned.
- The underlying message passing can be based on
 - raw sockets (no additional packages/software needed)
 - PVM (uses rpvm and PVM)
 - MPI (uses Rmpi and LAM-MPI; other MPIs may also work)
- Which communication mechanism is used only matters at startup.

Text on this slide is from a lecture by Luke Tierney in 22S:195 Fall 2007.

What to do when a computing problem is too big, or computing would take toolong, for a single computer to hande

- parallel computing
- using graphical processing units for mathematical calculations
- distributed and grid computing

Simple example of parallel computing in R

```
# R session on node 11 of the statistics cluster
> library(snow)
# establish communication with 10 other cores on 3 nodes
> cl <- makeSOCKcluster( c("node11","node11","node11","node12","node12",</pre>
"node12", "node12", "node13", "node13", "node13"))
# execute the Sys.info() function on all 10 worker cores, and retrieve
      just the nodename from it
> do.call("rbind", clusterCall(cl, function(cl) Sys.info()["nodename"]))
      nodename
 [1,] "node11.beowulf.stat.uiowa.edu"
 [2,] "node11.beowulf.stat.uiowa.edu"
 [3,] "node11.beowulf.stat.uiowa.edu"
 [4,] "node12.beowulf.stat.uiowa.edu"
 [5,] "node12.beowulf.stat.uiowa.edu"
 [6,] "node12.beowulf.stat.uiowa.edu"
 [7,] "node12.beowulf.stat.uiowa.edu"
 [8,] "node13.beowulf.stat.uiowa.edu"
 [9,] "node13.beowulf.stat.uiowa.edu"
[10,] "node13.beowulf.stat.uiowa.edu"
> x <- 1:100/101
```

time a computation on this vector done sequentially on the master node

> system.time(qtukey(x, 2, df=2))
user system elapsed

```
# time the same computation done in parallel on the 10 nodes in the cluster;
# the parLapply function sends equal-length segments of the vector to each
# core; each core does the computation on its segment; then the results
# are sent back to the master node and assembled there

> system.time(unlist(parLapply(cl, x, qtukey, 2, df=2)))
    user system elapsed
    0.004    0.000    0.543

> speedup <- 4.629/0.543
> speedup
[1] 8.524862

# shut down the communication among the cluster cores before leaving R
```

General programming with graphical processing units

- high end graphics cards such as those used in gaming computers have many cores for rendering graphics (up to several hundred)
- recently languages and programming toolkits have been developed to enable the use of the cores in graphics cards for mathematical computation
- challenges are the same as parallel processing on a cluster
 - has to be possible to divide the whole computing job (or parts of it) into individual small tasks that can be executed independently in parallel
 - slow transfer of data and results between CPU (regular processor) and GPU (graphics processor)

Distributed or grid computing

- distributed system: system of autonomous computers that communicate through a computer network to work together to solve a common computational problem
- distributed computing: use of distributed systems to solve computational problems
 - whole problem split into individual tasks, each carried out by single computer
- \bullet organizational grids

> stopCluster(cl)

• volunteer computing

The TeraGrid: example of a scientific grid

See some slides in separate lecture.

Blue Waters

http:

//www.ncsa.illinois.edu/enabling/bluewaters

Volunteer computing

- distributed computing in which computer owners donate some of their computer resources to one or more projects
- what kinds of computing problems are suitable
- BOINC software
- World Community Grid
 - an example of a well-run volunteer grid computing project
 - purpose and organization